

| Normen | Artikel | Abmessung | | Anmerkung | Wandstärken | Materialgüten |
|-------------|--|----------------------------|---|----------------------------|--|--|
| | | Rohranschluss inch | Rohranschluss mm | | | |
| DIN 2609 | Rohrbogen L.R. | 45° | 1/2" - 24" | 21,3 - 610,0 | ab 26" - 48" geschweißt | <p>WPB, WPC, WPL6, St35.8I, St35.8III, P235GH-TC1, P265GH-TC2</p> <p>WP1, WP5, WP9, WP11, WP22, WP91, 16Mo3, 13CrMo4-5</p> <p>L290NB, L360NB, L360QB, L415NB, L415QB, WPHY42, WPHY52, WPHY60, WPHY65, WPHY70</p> <p>1.4541, 1.4571, WP304, WP316</p> <p>S235, S355, 10CrMo 9-10</p> |
| | | 90° | 1/2" - 24" | 21,3 - 610,0 | | |
| | | 180° | 1/2" - 10" | 21,3 - 273,0 | | |
| EN 10253-2 | Rohrbogen S.R. | 45° | 1/2" - 16" | 21,3 - 406,4 | <p>von Sched 10 - Sched 160 / XXS 2,11mm - 59,54mm alle Wanddicken</p> | |
| | | 90° | 1/2" - 16" | 21,3 - 406,4 | | |
| | | 180° | 6" - 16" | 168,3 - 406,4 | | |
| ASME B16.9 | T-Stücke und reduzierte T-Stücke | 1/2" - 24" | | ab 26" - 48" geschweißt | | |
| | Exz. T-Stücke | 6" - 12" | 168,3 - 323,8 | | | |
| ASME B16.28 | Kreuz-T-Stücke | 8"x6" / 10"x8" / 12"x6" | 219x168 / 244x168 / 244x219 / 273x219 / 323x168 | ab 14mm Wanddicke | | |
| | Reduzierungen konz. | 1/2" - 24" | 21,3 - 610,0 | ab 26" - 48" geschweißt | | |
| | Reduzierungen exz. | 1/2" - 24" | 21,3 - 610,0 | | | |
| | Kappen | 1/2" - 24" | 21,3 - 610,0 | | | |
| | Sattelstützen | 1/2" - 24" | 21,3 - 610 | Wanddicke Reihe 1-4 | | |

Weitere Materialgüten, Abmessungen und Wandstärken auf Anfrage

| | | | |
|---|--|--|---|
|  | Wilhelm Geldbach Industrie GmbH Ziegelstrasse 17 D-45886 Gelsenkirchen | Telefon: +49 (209) 15803-0 Telefax: +49 (209) 22096 |  |
| | E-Mail: info@w-g.de Internet: www.w-g.de | | |